

CATALOGUE / IP FOG MACHINES / BASE ULTIMATE 110 V



BASE ULTIMATE 110 V

The ultimate is a powerful fog machine with unique direct heating.

It requires only the shortest possible heating time (2 sec.) and also has a stainless steel housing with IP64 protection class. The possible applications are varied and range from theme parks and fire drills to large stages.

[Manual \(English\)](#)

[Bedienungsanleitung \(Deutsch\)](#)

- FEATURES
- SPECIFICATIONS
- GALLERY
- RELATED PRODUCTS

FEATURES

IP64 Outdoor fog machine

- 1500 W.
- 2 SEC WARM UP TIME.
- 1,3"OLED-DISPLAY.

SPECIFICATIONS

Instant vaporizing fog machine

Connection Data	90-120 V~, 60 Hz, 1500 W (PowerCON TRUE1)
Warm up time	2 seconds
Fluid bottle	5 Liter or 1.32 Gallons

Fluid consumption	Up to 45ml/min
Operation	1.3" OLED-Display
CFM (Cubic Feet per Minute)	35,000 CFM
Communication interface	5 pol XLR In/out DMX, Aux-In (Analog 0-10V)
Supported protocols	DMX512, RDM, direct by SPS controllable (24V)
Control	DMX, analog, integrated timer, stand a lone mode
Protection class	IP64
Approved, tested fluids*	Hazebase BaseR - Quick Dissipating Hazebase BaseF - High Density
Weight	12.5 kg or 27.5 lbs
Dimensions (LxBxH)	487x200x235 mm (height with fluid basket: 388mm) or 19.2 x 7.9 x 9.3 inches (height with tank holder 15.3 inches)

GALLERY

Ultimate fog machine



RELATED PRODUCTS

Related products, options, and accessories



Base Fog Fluid Base R

Base Fog Fluid has been specially formulated to work in any situation.



Base Fog Fluid Base F

Base Fog Fluid has been specially formulated to work in any situation.