

[CATALOGUE](#) / [FOG AND HAZER MACHINES](#) / [HIGHPOWER² FROM HAZEBASE](#)

HIGHPOWER² FROM HAZEBASE

For maximum fog power.

Compact design and powerful 3100W output are complemented by the efficient and variable output, this machine is designed for versatility, efficiency, and reliability. The Highpower² reaches operation in less than 8 minutes. It can be controlled via DMX512, RDM, Modbus RTU or JT remote, or built-in onboard timer. Wired and wireless controllers are also available. Base Classic water-based fluid is designed for any environment. From a quick dissipation to a dense fog that will hang in the air. The unit can run continuously at 20%.

[Manual \(English\)](#)

[Bedienungsanleitung \(Deutsch\)](#)

[FEATURES](#)[SPECIFICATIONS](#)[GALLERY](#)[RELATED PRODUCTS](#)

FEATURES

For maximum fog power

- CONTROL VIA DMX512, RDM, MODBUS RTU, JT REMOTE, XLR WIRED REMOTE, WIRELESS REMOTE OR A VARIABLE STAND-ALONE BUILT-IN TIMER OR DMX OPERATION.
- GERMAN MADE, INTERNAL PUMPS ARE FITTED WITH SHOCK ABSORPTION.
- THE HIGHPOWER² IS EITHER AN EFFICIENT 3100-WATT 230V/50-60HZ. FULL OPERATION IS ACHIEVABLE IN LESS THAN 8 MINUTES.
- EFFICIENT FLUID CONSUMPTION RANGES FROM 300 ML/MIN AT MAXIMUM OUTPUT TO 70 ML/MIN WITH CONTINUOUS FOG.
- FOUR CHOICES OF PHARMACEUTICAL GRADE, WATER-BASED FLUID DESIGNED SPECIFICALLY FOR HAZEBASE.
- CONTROL ACCESSORIES ARE AVAILABLE FOR COMPLETE VERSATILITY FOR MULTIPLE APPLICATIONS.

SPECIFICATIONS

Efficient fluid consumption

Power

230V~, 50-60 Hz, 3100 W
(PowerCON TRUE1)

Heating time	Approx. 8 min
Fluid consumption	Up to 300 ml/min (full power mode, wide jet nozzle) Up to 70 ml/min with continuous fog
Tank Capacity	5 Liter or 1.32 Gallons
Unit Operation	1.3 "OLED display, membrane keyboard
Interfaces	5-pin XLR In / Out
Fog nozzles (exchangeable)	Wide-jet nozzle Noise reduction nozzle
Fog output	Adjustable 1-100% in 1% steps
CFM (Cubic Feet per Minute)	70,000 CFM
Output distance	Up to 20 m at Wide beam nozzle Up to 15 m with noise reduction nozzle
Supported protocols	DMX512, RDM, Modbus RTU, JT remote
Control	DMX / RDM, cable remote control, radio remote control, integrated timer, stand alone
Accessories (optional)	Radio remote control, cable remote control
Fog time	Up to 20 sec. In full power mode Up to 50 seconds. In full-time mode Permanent fog in non-stop
Fluid types	Base * X (extremely long-lasting) Base * L (long-lasting) Base * M (normal lasting) Base * Q (quick dissipating)
Dimensions (LxWxH)	480 x 212 x 240 mm (Height with tank holder 388 mm) or 18.9 x 8.3 x 9.4 inches (height with tank holder 15.3 inches)
Weight	14.0 kg or 30.8 lbs
Ambient temperature	+ 5 °C to 45 °C

GALLERY

Compact design and powerful 3100W output





RELATED PRODUCTS

Related products, options, and accessories



HazeBase Fog Fluid Base X

HazeBase Fog Fluid has been specially formulated to work in any situation.



HazeBase Fog Fluid Base M

Medium long lasting smoke liquid.



HazeBase Fog Fluid Base Q

Quick Dissipating Fog Fluid.